

STAPLES

CHISEL TIP

CERTIFICATIONS




They can be used in structural timber constructions to connect various elements together and for load-bearing connections between timber-based panels.



These staples are suitable for securing plasterboard panels.

STAPLE TIPS




On request, certain staple types can also be supplied with a tip other than the chisel tip.

STAPLES K

CHISEL TIP

- Staple type (BeA): **380**




Zn
ELECTRO
PLATED

CODE	L		coating	compatible machine	pcs	weight
	[mm]	[in]				
HH10000731	6	1/4	electrogalvanized	●	24000	2,3
HH10000736	8	5/16	electrogalvanized	●	21000	2,4
HH10000741	10	3/8	electrogalvanized	●	18000	2,3
HH10000750	12	1/2	electrogalvanized	●	15000	2,2
HH10000754	14	9/16	electrogalvanized	●	15000	2,5
HH10000758	16	5/8	electrogalvanized	●	12000	2,3

STAPLES C

CHISEL TIP

- Staple type (BeA): **90**




CODE	L		coating	surface	compatible machine		pcs	weight [kg]
	[mm]	[in]			HH3481	HH3489		
HH10004105	9	3/8	electrogalvanized	resin-coated	●	●	9800	1,6
HH10002642	12	1/2	electrogalvanized	resin-coated	●	●	7000	1,6
HH10002643	16	5/8	electrogalvanized	resin-coated	●	●	6000	1,7
HH10002644	19	3/4	electrogalvanized	resin-coated	●	●	5000	1,7
HH10002946	22	7/8	electrogalvanized	resin-coated	●	●	4000	1,5
HH10002646	25	1	electrogalvanized	resin-coated	●	●	3000	1,4
HH10003179	28	1 1/8	electrogalvanized	resin-coated	●	●	3000	1,5
HH10002648	29	1 1/8	electrogalvanized	resin-coated	●	●	3000	1,6
HH10002649	32	1 1/4	electrogalvanized	resin-coated	●	●	3000	1,7
HH10002650	35	1 3/8	electrogalvanized	resin-coated	●	●	2000	1,3
HH10002651	38	1 1/2	electrogalvanized	resin-coated	●	●	2000	1,4
HH10002652	41	1 5/8	electrogalvanized	resin-coated	●	●	2000	1,4

STAPLES KG

CHISEL/CD TIP

- Surface: **resin-coated**




CODE	L		coating	surface	compatible machine					pcs	weight [kg]	
	[mm]	[in]			HH3450	HH3455	HH3454	HH3727	HH3718			SKATER + HH12200126
HH10005561	30	1 3/16	electrogalvanized	●	●				●		9800	1,6
HH10005562	35	1 3/8	electrogalvanized	●	●		●	●			7000	1,6
HH10005563	40	1 9/16	electrogalvanized	●	●	●	●	●			6000	1,7
HH10005564	45	1 3/4	electrogalvanized	●	●	●	●	●	●		5000	1,7
HH10005565	50	1 15/16	electrogalvanized	●	●	●	●	●	●	●	4000	1,5
HH10005566	55	2 3/16	electrogalvanized			●	●	●	●	●	3000	1,4
HH10005567	65	2 9/16	electrogalvanized			●	●	●	●	●	3000	1,5
HH10005700	40	1 9/16	stainless A2 (AISI 304)	●	●	●	●	●			5000	6,5
HH10005701	45	1 3/4	stainless A2 (AISI 304)	●	●	●	●	●	●		5000	7,3
HH10005702	50	1 15/16	stainless A2 (AISI 304)	●	●	●	●	●	●		5000	8,0
HH10005699 ⁽¹⁾	25	1	electrogalvanized	●	●						6300	5,5

⁽¹⁾ With CD tip, particularly suitable for double-layered fibre cement panels.

STAPLES Q

CHISEL TIP


- Staple type (BeA): **180**



CODE	L		coating	surface	compatible machine		pcs	weight [kg]
	[mm]	[in]			HH3727	SKATER + HH12200125		
HH10005874	45	1 3/4	electrogalvanized	resin-coated	●	●	4320	8,9
HH10005875	50	1 15/16	electrogalvanized	resin-coated	●	●	4320	9,4
HH10005876	55	2 3/16	electrogalvanized	resin-coated	●	●	4320	10,2
HH10005877	63	2 1/2	electrogalvanized	resin-coated	●	●	4320	11,6
HH10005213	50	1 15/16	stainless A2 (AISI 304)	resin-coated	●	●	10000	23,3
HH10005216	63	2 1/2	stainless A2 (AISI 304)	resin-coated	●	●	10000	29,1

STAPLES G

CHISEL TIP




CODE	L		coating	surface	compatible machine			pcs	weight [kg]
	[mm]	[in]			HH3450	HH3718			
HH10005185 ^(*)	25	1	electrogalvanized	resin-coated	●			5000	4,2
HH10005187 ^(*)	29	1 1/8	electrogalvanized	resin-coated	●			5000	4,7
HH10005190	32	1 1/4	electrogalvanized	resin-coated	●		●	5000	5,2
HH10005193	35	1 3/8	electrogalvanized	resin-coated	●		●	5000	5,5
HH10005197	38	1 1/2	electrogalvanized	resin-coated	●		●	5000	6,1
HH20006020	41	1 5/8	electrogalvanized	resin-coated	●		●	5000	6,8
HH20006025	45	1 3/4	electrogalvanized	resin-coated	●		●	5000	7,2
HH20006030	50	1 15/16	electrogalvanized	resin-coated	●		●	5000	8,1
HH10005209	57	2 1/4	electrogalvanized	resin-coated			●	5000	9,3
HH10005211	64	2 1/2	electrogalvanized	resin-coated			●	5000	9,9
HH10005204	45	1 3/4	stainless A2 (AISI 304)	resin-coated	●		●	5000	7,1
HH10005206	50	1 15/16	stainless A2 (AISI 304)	resin-coated	●		●	5000	8,0
HH10005210	64	2 1/2	stainless A2 (AISI 304)	resin-coated			●	5000	10,2

^(*) Not CE-certified.

STAPLES BS

CHISEL TIP

- Staple type (BeA): **246**



CODE	L		coating	surface	compatible machine			pcs	weight [kg]
	[mm]	[in]			HH3474	TJ100689	SKATER + 12200128		
HH20005278	75	2 15/16	electrogalvanized	resin-coated	●	●	●	2160	12,5
HH10005296	90	3 1/2	electrogalvanized	resin-coated	●	●	●	1920	10,0
HH10005551	100	4	electrogalvanized	resin-coated	●	●	●	2860	16,9
HH10005295 ^(*)	110	4 3/8	electrogalvanized	resin-coated	●	●	●	1600	9,8
HH10005552	130	5 1/8	electrogalvanized	resin-coated	●	●	●	1420	10,2
HH10004885 ^(*)	150	6	electrogalvanized	resin-coated		●		960	8,0
HH10005272	75	2 15/16	stainless A2 (AISI 304)	resin-coated	●	●	●	2860	11,8
HH10005273	100	4	stainless A2 (AISI 304)	resin-coated	●	●	●	2860	16,3
HH10005274	110	4 3/8	stainless A2 (AISI 304)	resin-coated	●	●	●	2850	17,7
HH10005275	120	4 3/4	stainless A2 (AISI 304)	resin-coated	●	●	●	1420	10,3
HH10005276	130	5 1/8	stainless A2 (AISI 304)	resin-coated	●	●	●	1420	10,3
HH10004906 ^(*)	150	6	stainless A2 (AISI 304)	resin-coated		●		960	7,9

^(*) On demand.