


POINTES EN BANDE, BOBINAGE EN PLASTIQUE K20°

CLOUS LISSES


EN BANDE - K20 °



d ₁ [mm]	CODE	L [mm]	revêtement	machines compatibles			pcs	poids [kg]
				HH3555	HH12100697	HH12100698		
2,8	HH10400015	60	sans galvanisation	●			3000	9,0
	HH10400020	65	sans galvanisation	●			3000	9,8
	HH10400029	70	sans galvanisation	●			3000	10,5
3,1	HH10400030	70	sans galvanisation	●			3000	12,8
	HH10400044	80	sans galvanisation	●			3000	14,6
	HH10400054	90	sans galvanisation	●			3000	16,5
3,4	HH10401635	100	sans galvanisation	●			2500	17,4
3,8	HH10400077	100	sans galvanisation	●	●	●	1500	13,5
	HH10400060	110	sans galvanisation		●	●	1500	14,9
	HH10400062	120	sans galvanisation		●	●	1500	16,3
	HH10400067	130	sans galvanisation		●	●	1500	17,7
	HH10400063	120	sans galvanisation		●	●	1500	20,0
4,2	HH10400068	130	sans galvanisation		●	●	1500	21,6
	HH10400494	145	sans galvanisation			●	660	11,6
	HH10400605	150	sans galvanisation			●	660	10,9
	HH10400402	160	sans galvanisation			●	660	11,4
4,6	HH10400069	145	sans galvanisation			●	660	13,5
	HH10400070	160	sans galvanisation			●	660	14,1
2,8	HH10401476	65	électrozingué	●			4000	13,4
	HH10401480	80	électrozingué	●			4000	16,1
3,1	HH10401483	70	électrozingué	●			4000	16,8
	HH10400041	80	électrozingué	●			3000	14,6
	HH10400051	90	électrozingué	●			3000	16,5
3,4	HH10401636	100	électrozingué	●			2500	17,4
3,8	HH10401683	100	électrozingué	●	●	●	1500	14,9
	HH10401620	110	électrozingué		●	●	1500	14,9
	HH10400197	120	électrozingué		●	●	1500	16,2
	HH10400065	130	électrozingué		●	●	1500	17,7
4,2	HH10401647	130	électrozingué		●	●	1500	21,0
4,6	HH10400006	160	électrozingué			●	660	13,5

CLOUS RING

EN BANDE - K20 °



d ₁ [mm]	CODE	L [mm]	revêtement	machines compatibles			pcs	poids [kg]
				HH3555	HH12100697	HH12100698		
2,8	HH10401519	65	sans galvanisation	●			4000	13,2
	HH10401521	70	sans galvanisation	●			4000	14,4
	HH10401523	80	sans galvanisation	●			4000	15,8
3,1	HH10401524	70	sans galvanisation	●			4000	16,5
	HH10401687	80	sans galvanisation	●			3000	14,6
	HH10400412	90	sans galvanisation	●			3000	16,4
3,8	HH10401632	120	sans galvanisation		●	●	1500	16,1
	HH10400462	130	sans galvanisation		●	●	1500	17,7
4,2	HH10401130	160	sans galvanisation			●	660	11,4
4,6	HH10401648	160	sans galvanisation			●	660	12,2
2,8	HH10401520	65	électrozingué	●			4000	13,2
	HH10400034	75	électrozingué	●			3000	11,2
3,1	HH10400945	70	électrozingué	●			4000	16,9
	HH10401888	80	électrozingué	●			3000	14,6
	HH10401834	90	électrozingué	●			3000	16,0
3,8	HH10401645	130	électrozingué		●	●	1500	17,7