

PRIMER SPRAY

UNIVERSAL SPRAY PRIMER FOR ACRYLIC ADHESIVE TAPES


INSTANTANEOUS

Thanks to spray can application and the adjustable nozzle, no brushes or other equipment is needed for installation.

HIGH PERFORMANCE

At a distance of approx. 30 - 50 cm from the surface approx. 6 cm of gluing area is achieved.

Ideal for use with Rothoblaas tapes.



TECHNICAL DATA

Properties	value	USC units
Composition	mix of thermoplastic adhesive and solvent	-
Time required for drying 20 °C/50 %RH	1-2 minutes	-
Application temperature (cartridge, ambient and support)	+15/+25°C	+59/+77 °F
Temperature resistance after drying	-10/+100°C	+14/+212 °F
French VOC classification	A+	-
Transport temperature	+5/+50°C	+41/+122 °F
Storage temperature ⁽¹⁾	+15/+35 °C	+59/+95 °F

⁽¹⁾Store the product in a dry place and check the date of manufacture on the cartridge.

Waste classification (2014/955/EU): 16 05 04.
Aerosol 1 - H222, H229.

CODES AND DIMENSIONS

CODE	content [ml]	content [US fl oz]	
PRIMERSPRAY	750	25.36	12



FAST INSTALLATION

It allows smoothing of even the roughest and most fibrous surfaces to facilitate the application of tapes or sealants.

ADJUSTABLE

Adjustable nozzle for a more precise application adapted to each situation. Simply turn the nozzle to increase or decrease the spray area.