

# RIDGE

## NET ROLL

### FLEXIBLE VENTILATED UNDER-RIDGE

#### FLEXIBLE

The polypropylene ventilation fabric ensures excellent adaptability during installation.

#### DOUBLE SECURITY

The ventilation strip, which is sewn and glued to the pleated wings, guarantees that the solution remains intact during installation and continues to be effective over time.




### TECHNICAL DATA

Properties	value	USC units
Air passage	approx. 150 cm <sup>2</sup> /m	7.09 in <sup>2</sup> /ft
Elongation capacity (pleated aluminium strips)	approx. 45 %	-
Butyl tape width	15 mm	0.6 in
Butyl tape thermal resistance	-40 / +90 °C	-40 / +194 °F
Application temperature	+5 / +40 °C	+41 / +104 °F
UV resistance (aluminium straps)	permanent	-
Storage temperature <sup>(1)</sup>	+5 / +30 °C	+41 / +86 °F

<sup>(1)</sup> Keep the product in a dry, covered location.

Waste classification (2014/955/EU): 17 09 04.

### CODES AND DIMENSIONS

CODE	B [mm]	L [m]	B [in]	L [ft]	colour	RAL	
NETRED310	310	5	12.2	16	brick red	8004	4
NETBRO310	310	5	12.2	16	brown	8019	4
NETBLA310	310	5	12.2	16	black	9005	4
NETRED390	390	5	15.4	16	brick red	8004	4
NETBRO390	390	5	15.4	16	brown	8019	4
NETBLA390	390	5	15.4	16	black	9005	4
NETRED39020	390	20	15.4	66	brick red	8004	1
NETBRO39020	390	20	15.4	66	brown	8019	1
NETBLA39020	390	20	15.4	66	black	9005	1



#### EASY TO SHAPE

Aluminium straps and butyl tape ensure adaptability to the profile of the roof elements.

#### MATERIALS

Aluminium, PP non-woven fabric, butyl tape.