

AOS

ANCHOR POINT

UNIVERSAL

The threaded rod available in various lengths allows the anchor to adapt to any type of timber, concrete and steel structure.

FUNCTIONAL

The 360° swivel eyelet allows the operator total freedom of movement on the roof.

COMPLETE

Supplied in a handy kit complete with bolts and washers for installation.

EN
795:2012
A

CEN/TS
18419:2013

UNI
11578:2015
A



MAXIMUM NUMBER
OF USERS



LOAD DIRECTION



TYPES OF
APPLICATION



MY
PROJECT
SAFETY




TECHNICAL DATA*

substructure	minimum thickness
GL24h	100 x 120 mm
S235JR	5 mm

substructure	minimum thickness	fasteners
C20/25	164 mm	VIN-FIX HYB-FIX


* The values indicated are the result of experimental tests carried out under the supervision of third parties in accordance with the standards referred to. For a correct calculation report with minimum distances according to the standard requirements, the substructure must be checked by a qualified engineer before installation.

CODES AND DIMENSIONS

CODE	material	max. thickness of fixture		H		pcs	
		[mm]	[in]	[mm]	[in]		
AOS50	AISI 304 stainless steel grade 1.4301	29	1 1/8	80	3 1/8	1	
AOS50A4	AISI 316 stainless steel grade 1.4401	29	1 1/8	80	3 1/8	1	
AOS130	AISI 304 stainless steel grade 1.4301	132	5 3/16	175	6 7/8	1	
AOS130A4	AISI 316 stainless steel grade 1.4401	132	5 3/16	175	6 7/8	1	
AOS200	AISI 304 stainless steel grade 1.4301	164	6 7/16	250	10	1	
AOS300		264	10 3/8	350	13 3/4	1	
AOS400		364	14 5/16	450	17 3/4	1	
AOS500		464	18 1/4	550	21 5/8	1	
AOS200A4	AISI 316 stainless steel grade 1.4401	164	6 7/16	250	10	1	
AOS300A4		264	10 3/8	350	13 3/4	1	
AOS400A4		364	14 5/16	450	17 3/4	1	
AOS500A4		464	18 1/4	550	21 5/8	1	

ACCESSORIES

CODE	description	page
OMEGA	accessory for MULTIPLATE	253



CODE	description	page
MULTIPLATE	fixed counterplate	253

